



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61B 5/00 // G06F 3/033	A1	(11) International Publication Number: WO 98/11820
		(43) International Publication Date: 26 March 1998 (26.03.98)

(21) International Application Number: PCT/SE97/01587

(22) International Filing Date: 19 September 1997 (19.09.97)

(30) Priority Data:

9603429-3 19 September 1996 (19.09.96) SE

9603428-5 19 September 1996 (19.09.96) SE

(71) Applicant (for all designated States except US): SVENSKA
TELEMEDICIN SYSTEM AB [SE/SE]; F.O. Petterssons
gata 32, P.O. Box 237, S-421 23 Västra Frölunda (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SJÖQVIST, Bengt, Arne
[SE/SE]; Tåmeskärgatan 28, S-421 57 Västra Frölunda
(SE).(74) Agent: AWAPATENT AB; P.O. Box 11394, S-404 28
Göteborg (SE).(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ,
BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility
model), DE, DE (Utility model), DK, DK (Utility model),
EE, EE (Utility model), ES, FI, FI (Utility model), GB,
GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK,
LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO,
NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility
model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU,
ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB,
GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ,
CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.


Before the expiration of the time limit for amending the
claims and to be republished in the event of the receipt of
amendments.

In English translation (filed in Swedish).

(54) Title: PORTABLE TELEMEDICIN DEVICE

(57) Abstract

A portable telemedicine device for use in preliminary diagnostic procedures and treatments, comprising a data processing unit (1), measurement means and the like, and a presentation means, such as a screen. Characterising features of the device are that it further comprises entry means for manual input of information data, and communication equipment (2) for bi-directional communication with another, preferably stationary central unit (3).



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

PORTABLE TELEMEDICIN DEVICETechnical Field

The present invention concerns a portable telemedicine device for use in preliminary diagnostic procedures and treatments.

5

Background

The normal procedure in the case of serious illnesses is to transport the patient to a hospital for diagnosis and treatment of the illness. However, it has
10 proved to be advantageous to arrange for the nursing or ambulance staff to carry out the diagnosis and to start the treatment already at the place of patient pick-up. Such an arrangement likewise makes it possible to establish at an early stage whether a particular
15 specialist competence and special equipment or the like are required, whereafter the patient may be transported straight to the place where such competence, equipment etcetera are available.

Such early diagnosis and treatment would be
20 considerably facilitated, were the nursing staff given a possibility to carry with them a portable telemedicine device adapted to register signals from ECG and VCG units and similar sensing equipment. A portable unit of this kind, which may be docked and thus be connected to a
25 stationary communications network (LAN), which allows connection thereto of external measurement equipment, and which comprises a display device for visualisation of the measurement results, is disclosed in US 5 375 604.

However, this prior-art device is merely a passive
30 unit and it is designed for reception and visualisation only of signals from the measurement equipment. It cannot be used to establish active contact with and an exchange of information between the patient-attending staff and

other individuals, a possibility which could be helpful in the diagnosis procedure as well as for the implementation of correct treatment measures. This is true particularly in the case of the above portable unit when
5 used un-docked, in which case there is no communication with other equipment.

Furthermore, US 5 441 047 describes a system according to which selected data on the patient is collected automatically, whereupon said data are forwarded via a stationary telecommunication network, such
10 as a cable television network, to a centre where the diagnosis, monitoring or similar operations may be performed. The referred-to equipment is not, however, portable and in addition it comprises a plurality of
15 independent components, and consequently this equipment is not adapted for ambulatory use and positioning onboard e.g. an ambulance. Nor is it adapted for active exchange of information between the nursing staff by the patient's side and the personnel at the central unit.

20 In addition, there is a need for message exchanges between the nursing staff by the patient's side and the personnel at the central unit as well as for possibilities of filling in certain types of pre-defined forms, such as patient case record files, already in the initial
25 stage by the patient's side. These needs are not met in the prior-art devices.

In addition, it would be desirable, were it possible to enter data manually and preferably by one hand only, in a convenient, rapid and simple manner. It would
30 likewise be desirable, were it possible to construct the entry means sufficiently small not to make the portable equipment unnecessarily voluminous and unmanageable.

Purpose of the Invention

35 The object of the present invention thus is to provide a portable telemedicine device which completely

or at least partly eliminates the problems encountered in connection with the prior-art technology.

This object is achieved in a device as defined in claim 1.

5

Brief Description of the Drawing Figures

In the drawing figures:

Fig. 1 is a schematic view of a system comprising a portable telemedicine device in accordance with the invention;

10

Fig. 2 is a view of a preferred embodiment of the portable telemedicine device of Fig. 1;

Fig. 3 illustrates a first example of a display layout intended for use together with the device of Fig. 2; and

15

Fig. 4 illustrates a second example of a display layout intended for use together with the device of Fig. 2.

Detailed Description of Preferred Embodiments

20

The invention will be described in closer detail in the following for exemplifying purposes with reference to the accompanying drawings.

As shown in Fig. 1, the invention comprises a portable telemedicine device 1 including integrated measuring equipment, such as ECG and VCG, input means for connecting external measuring sensors, a display for displaying the measurement data and the like, entry means for entry of other measurement data, patient's name, observations and so on, and communication equipment 2. The portable telemedicine device in accordance with the invention preferably is an easily manageable, integrated unit, illustrated in Fig. 2. Preferably, this unit is also provided with a rechargeable battery unit, which adds to the ambulatory nature of the device.

35

Again referring to Fig. 1, the communication equipment 2 may be arranged to transmit digital data via a

mobile telephone network, such as GSM or the like, via the MOBITEK network or by any other suitable means. Thus, the telemedicine device may communicate directly with one or several central units 3 or via one or several intermediate stations, such as for instance an ambulance 4. Optionally, the communication may be established via option communication means, such as GSM and MOBITEK, as selected in accordance with the conditions in each individual case.

10 Preferably, the central units are data-processing devices capable of receiving information data and presenting the latter in real time, and also capable of emitting information data to portable units. The central unit preferably also is capable of communicating with
15 other systems, of storing information data, and of later displaying such stored information data. However, central units of this nature are previously known within the technical field concerned and the design of these units does not form part of the present invention, although
20 they do form part of a system comprising the portable telemedicine device in accordance with the invention.

The portable telemedicine device is further advantageously equipped with a connecting interface for allowing convenient docking thereof to stationary
25 equipment 5, e.g. onboard an ambulance or inside a hospital. The docking interface may be designed to shift its mode of communication at the instance of docking, to allow transmission via another telecommunication network or via cables coupled to the stationary equipment. In
30 addition, the docking may involve connection to network voltage, battery chargers, external entry means (such as keyboards), external displays, and so on. Optionally, the portable telemedicine device could likewise be adapted for communication via IR transmission using prior-art
35 equipment, such as PDA equipment (Personal Digital Assistant) and the like.

The device may also be adapted for automatic selection of a telecommunication network in response to the current reception conditions, in order thus to offer the best possible transmission performance. Such adaptation could likewise depend on the type of information data to be transmitted and on the manner of the transmission. In this way it becomes possible to use different networks for transission for example of large data volumes that must be transmitted to a receiver within a brief space of time, and of short messages that are to be transmitted to several receivers. For instance, the device may utilise networks of such a different nature as the circuit-switched GSM network and the packet-switched MOBITEK. However, to achieve this versatility feature, adaptations are required in the form of different software as well as different hardware. To make it possible to use such a comparatively slow transmission system as the MOBITEK, selection and pre-processing of data are required as is also compressing of these data.

When the portable telemedicine equipment is intended for use by ambulance staff or other ambulant personnel, it is advantageously brought along when the ambulance staff is called to the patient. The sensors associated with ECG, VCG etcetera are connected, and a first diagnosis may then be made. In some cases it may, however, be more appropriate to defer connection of the equipment until the patient is onboard the ambulance.

The display preferably is divided into different fields, showing for example:

- Information on the patient's name, patient ID number, time, and so on;
- Monitoring information received from the measuring equipment, such as continuous ECG monitoring, blood pressure monitoring, continuous curves indicating the variations in the oxygenation of the blood, and so on;
- ECG reports, "cuttings" from real-time curve graphs,

tendencies, patient case record files, other information, recently received messages, and so on;

- Up-to-date values of collected measurement data and set alarm limits;
- 5 • Menu of currently selectable commands;
- Status of communication equipment, such as available connected receivers and the band width of the communication channel;
- Messages received and emitted, inclusive of
- 10 facilities for browsing through old messages;
- Setting options, e.g. different communication networks, reception and transmission via ambulance or not, different areas of application, choice of external equipment to be
- 15 connected, and so on.

In addition, the menu system could advantageously be designed to comprise several levels, including one main menu and one or several levels including sub-menus.

Following connection of the equipment, information

20 data are entered, either automatically via the measuring instruments or manually by the patient-attending staff. Some information data, such as those relating to certain measurement results, annotations entered into patient case record files, patient information and so on, are

25 then transmitted automatically to the predetermined receivers to which the device is connected, whereas other information data are forwarded only as ordered by the attending staff. A transmission list determines which receivers are to be used in each individual case, from

30 which list one or several central units may be pre-selected. Preferably, the list may be altered in the process of use.

The information to be transmitted may be assigned different priorities, the information data most essential

35 for correct diagnosis and for the implementation of correct treatment being given a higher priority and being transmitted prior to information data of less importance.

This feature is particularly advantageous for instance when the capacity of the communication network is such that the latter is slow in transmitting the information and when it may not even be possible to transmit all
5 information. The priority feature may be implemented manually, or, which in most cases is the preferred alternative, automatically with the aid of software, or else a combination of the two varieties is possible. The medical usefulness should, at all times, govern the
10 priority.

In addition, the portable telemedicine equipment is supplied with information data from the central unit, on the one hand in the form of messages from e.g. specialist physicians, the co-ordinating control group, etcetera,
15 and on the other in the form of data from the patient's case record file and the like, data which are already stored in databases 6 in the central unit.

In addition to its use in showing measurement results, the portable telemedicine device in accordance
20 with the invention could also be used for filling in certain forms, such as patient's case record files and the like, in addition to which it offers facilities for communication with a central unit (or several central units) via the telecommunication network. The central
25 unit could be positioned e.g. in the closest large hospital where the received information data could be examined by specialist physicians of the relevant medical discipline and a correct decision be taken rapidly, both with respect to the treatment to be implemented right
30 away and to the planning and the preparations for the continued treatment. In other words, owing to the communication facility, measurement results and other entered information data are transmitted in full or in part from the portable telemedicine equipment to the
35 central unit, and the information data, which may include treatment counselling, queries relating to the diagnosis, information regarding where to transport the , and so on,

are transmitted from the central unit to the portable unit. In addition, all dialogue preferably should be stored in the portable unit and/or the central unit.

The various part components of the device are, as
5 already mentioned, preferably integrated in an easily manageable unit, thus making it simple to handle, and versatile and easy to transport and to connect.

Optionally, additional equipment could be included as parts of the device or be connectable thereto, such as
10 printers, cameras, microphones, loud-speakers, etcetera, depending on need, communication channel capacity and so on.

According to a particularly preferred embodiment the portabel unit is provided with an entry means of a
15 special design and forming part of the present invention.

As appears from Fig. 2, the entry means comprises a bottom plate 11 formed with an entry means consisting of a rotatable and depreciable actuating member 12 in the form of e.g. a ball or a wheel, and of additional entry
20 buttons 13 and 14. The actuating member affects a cursor on the display screen in such a manner that the cursor moves in response to actuation of the actuating member. The cursor is only movable backwards and forwards between points in a predetermined order. For instance, the cursor
25 movement could be upwards and downwards in a vertically arranged menu, jumping between a number of different windows on the screen or the like. Upon depression of the actuating member 12 the object highlighted at that moment by the cursor is activated (i.e. the function identical
30 to that of the "ENTER"-key on an ordinary keyboard). In this situation, either the indicated function is performed, involving for instance entering an object in the form, or else a sub-menu appears, whereupon the procedure is repeated.

35 In this manner it likewise becomes possible to enter text or figures, in that by turning the actuating member the operator may proceed through the entire alphabet or

the numbers and by depressing the member indicate the letters or figures he wants to enter.

Out of the extra entry buttons of the entry means, one button 13 is for verifying incoming messages or
5 alarms and one button 14 for moving to a superior menu level. In addition to these two buttons the entry means could be supplemented with numeric keys 15 representing digits 0-9 etcetera, in order to render the data input more efficient, should the entry items comprise several
10 measurement values in digit form. In addition, the entry means preferably comprises a delete button 16 to erase entered values.

An entry means in accordance with the invention occupies but a fraction of the space required by a
15 conventional keyboard, in addition to which it could advantageously be placed vertically, a position most unsuitable for conventional keyboards. For instance, an LCD display and an associated, e.g. juxtaposed entry means in accordance with the invention may easily be
20 placed in positions where conventional terminals cannot be used. In addition, the entry of input data may easily be effected using one hand only.

When the entry means is used as described above, the display preferably is divided into several fields, such
25 as shown for example in Fig. 3. In this drawing figure is illustrated one example of a display layout that may be used by the medical services and that comprises one field 21 containing information on the patient's name, identity number, information on the status of the communication
30 and similar comprehensive information, a second field 22 containing a presentation, for instance in the form of curve graphs, representing incoming measurement values and the like (e.g. from ECG), a third field 23 containing measurement data derived from other (or the same)
35 measurement instruments and alarm limits, and a fourth field 24 containing a menu of selectable options. As the actuating member is being rotated different menu options

will be highlighted in a predetermined order. This predetermined order could be e.g. from the top towards the bottom, or inversely, depending on the direction in which the operator rotates the actuating member. The highlighted option is activated upon depression of the actuating member, causing either the activation of a function or the appearance of a new sub-menu.

Fig. 4 illustrates one example of the configuration of a display upon activation of a "case record file" function for entering information data into the patient's case record file. Under this option heading, a sub-menu appears. In this case, the sub-menu comprises four different case record fields and three additional menu options. To enter data, the operator/attendant turns e.g. the actuating member 12, causing the first case record field to be highlighted, whereupon he depresses the actuating member to activate the highlighted field. In this field, there are two alternative choices: input of personal code number and input of personal name. As the personal code number is entered, this option is highlighted in the same manner as mentioned above, whereupon one digit at a time is entered. This could be achieved e.g. by means of a line of numbers which appears on the display and from which desired numbers are chosen through rotation and depression of the actuating member as indicated previously. Alternatively, the highlighted number is increased or decreased by means of rotation of the actuating member, followed by depression of the member, the corresponding number thus being chosen and the cursor made to proceed to the next position, wherein the procedure is repeated.

In order to return to the immediately superior menu the latter could either be permanently available as a last selectable menu option or else be retrieved by use of the particular return button. An entered digit could be cancelled/deleted with the aid of the button provided for this purpose.

Entry of letters is effected in the same manner as entry of figures, and figures as well as letters as also other signs may be selectable in all positions.

In addition, the entry procedure could in many cases
5 be simplified, when only a restricted amount of entry options exists or occurs frequently. In such cases, the data entry could be effected via a menu comprising predefined options, such as shown for example in the fourth, lowest case record field in Fig. 4. In this
10 field, the diagnosis, such as "angina pectoris", may be entered by advancing the cursor through rotation of the actuating member until the cursor reaches the relevant option, and by subsequently marking the latter as indicated above.

15 Several modifications of the entry means in accordance with the invention are conceivable. For instance, the entry means need not comprise supplementary entry buttons but the rotatable and depressible actuating member by itself suffices in many cases. In addition, the
20 actuating member could optionally be divided into two separate means, one of which is rotatable whereas the other is depressible. Several modifications of other parts of the invention are of course likewise possible. For example, other measurement equipment than that
25 mentioned in the foregoing may be coupled to the device. The device could furthermore be used in other applications involving services and activities related to nursing and attending of individuals, such as home-help services. Such closely related varieties of the invention
30 must be regarded to be within the scope of the invention as the latter is defined in the appended claims.

CLAIMS

1. A portable telemedicine device, preferably in the form of an integrated unit, for use in preliminary
5 diagnostic procedures and treatments, comprising a data processing unit (1), measurement means and the like, and a presentation means, such as a screen, c h a r a c -
t e r i s e d in that it further comprises entry means for manual input of information data, and communication
10 equipment (2) for bi-directional communication with one or several, preferably stationary central units (3).

2. A telemedicine device as claimed in claim 1, c h a r a c t e r i s e d in that it is intended for use outside medical-care centres, such as hospitals, clinics
15 and nursing homes.

3. A telemedicine device as claimed in claim 1 or 2, c h a r a c t e r i s e d in that means are arranged to assign different priorities to different types of transmitted information data, such as patient record file
20 data, physiological data, form data, numbers, images, and the like, upon transmission of said data to the central unit (3), ensuring that the information data of the highest priority in each current situation is transmitted first.

25 4. A telemedicine device as claimed in any one of the preceding claims, c h a r a c t e r i s e d in that the communication is adapted to be established via preferably wireless telecommunication networks.

5. A telemedicine device as claimed in claim 4, c h a r a c t e r i s e d in that the communication is adapted to be established via GSM and/or MOBITEX.
30

6. A telemedicine device as claimed in any one of the preceding claims, c h a r a c t e r i s e d in that it is dockable with, i.e. connectable to, a larger unit
35 (5), for instance a unit positioned onboard an ambulance (4).

7. A telemedicine device as claimed in claim 6, characterised in that it is adapted, when docking, to automatically change to another telecommunication network as the need arises.

5 8. A telemedicine device as claimed in any one of the preceding claims, characterised in that it is adapted to automatically select, among several possible telecommunication networks, the one most efficient in view of the current application.

10 9. A telemedicine device as claimed in any one of the preceding claims, characterised in that it is adapted to receive information data from the central unit, said data representing results from diagnoses, suggested care, previously stored data on the
15 patient, and the like.

10. A telemedicine device as claimed in any one of the preceding claims, characterised in that the entry means comprises a rotatable actuating member (12) by means of which a cursor on the presentation means
20 may be displaced and thus highlighting alternative objects in a predetermined order by made by rotation of the actuation member, and a depressible actuation member (12) for activating the current highlighted objects by depression of said member.

25 11. A telemedicine device as claimed in claim 10, characterised in that the rotatable and depressible actuating member is combined into one single actuating member (12).

30 12. A telemedicine device as claimed in claim 10 or 11, characterised in that the option objects to be highlighted form a main menu wherein each object may comprise several levels of sub-menus, said entry means also comprising a return button (13, 14) for return to the level above the current one.

1/4




Fig. 1

2/4




Fig. 2

3/4




Fig. 3

4/4

214385-8790 Putte Patient		CASE RECORD FILE
Personal Code No. 214365-8790 Name: Putte Patient		<div style="border: 1px solid black; padding: 5px; margin-bottom: 10px; text-align: center;">Change form</div> <div style="border: 1px solid black; padding: 5px; text-align: center;">Main Menu Text Stop</div>
BP syst _____ Resp. rate. 110 Saturation 98 BP diast _____ Pulse 127 Smart VAS ↓		
Eye movement 3 open when addressed firmly ↓ Motor response ↓ Verbal response ↓ GCS ↓		
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> Diagnosis suspected infraction angina pectoris heart failure diffuse chest pains </div> <div style="width: 45%;"> Skin <input type="checkbox"/> Normal <input type="checkbox"/> Damp <input type="checkbox"/> Pale <input type="checkbox"/> Cyanosis </div> </div>		
Priority before action ↓		<div style="border: 1px solid black; padding: 5px; text-align: center;">Main Menu</div>

Fig. 4

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01587

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: A61B 5/00 // G 06 F 3/033

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: A61B, G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	SE 9001549-6 A (K ELIS NORDEN), 31 October 1991 (31.10.91), page 3, line 49 - line 59; page 4, line 6 - line 10, claim 5	1-5,8-9
Y	--	10-12
X	EP 0707825 A2 (HEWLETT-PACKARD COMPANY), 24 April 1996 (24.04.96), column 14, line 31 - line 34; column 17, line 15 - line 59; column 18, line 1 - line 26, abstract	1-3,6-9
Y	--	10-12



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier document but published on or after the international filing date	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

Date of mailing of the international search report

19 December 1997

12-01-1998

Name and mailing address of the ISA/

Authorized officer

Swedish Patent Office

Malin Keijser

Box 5055, S-102 42 STOCKHOLM

Telephone No. +46 8 782 25 00

Facsimile No. +46 8 666 02 86

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01587

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0635781 A1 (XEROX CORPORATION), 25 January 1995 (25.01.95), column 9, line 16 - line 30; column 10, line 47 - line 54, figure 1 --	10-12
A	EP 0251520 A2 (BUDDY SYSTEMS, INC.), 7 January 1988 (07.01.88), page 4, line 35 - line 55; page 5, line 1 - line 44 --	1-4
A	EP 0669715 A1 (LOEWE OPTA GMBH), 30 August 1995 (30.08.95), column 6, line 20 - line 48, figure 1 -- -----	11

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 97/01587

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
SE 9001549-6 A	31/10/91	NONE	
EP 0707825 A2	24/04/96	JP 8237760 A US 5687734 A	13/09/96 18/11/97
EP 0635781 A1	25/01/95	CA 2124505 A JP 7056840 A	22/01/95 03/03/95
EP 0251520 A2	07/01/88	JP 63079643 A US 4803625 A	09/04/88 07/02/89
EP 0669715 A1	30/08/95	DE 4405962 C	01/06/95

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.